

PRODUCT PAGE

For technical and availability information,
please contact Onmar.

+46 (0) 16 42 86 80

info@onmar.com

www.onmar.com

STALON THRU HULL

Stainless Steel 316 Face & Nylon 66 +
30% Fiberglass Filled Body

- Combining the strength and light weight of a reinforced nylon with the aesthetics of polished stainless steel.
- Tested according to ASTM D638 and ASTM D790.
- M7-01-9005260: Barb angle is designed to eliminate trapped water in the drain hose.
- Suitable for above waterline outlets.





0°



15°

Part number	Angle	A (mm)	B	C	D	E (max mm)
M7-01-9005241	0°	16	75	33	48	29
M7-01-9005242	0°	19	81	33	48	29
M7-01-9005243	0°	26	79	33	48	29
M7-01-9005245	0°	32	96	41	60	32
M7-01-9005246	0°	38	96	41	60	32
M7-01-9005260	15°	38	166	56	83	83
M7-01-9005263	0°	19	138	33	48	86



90° STALON THRU HULL

Stainless Steel 316 Face & Nylon 66 +
30% Fiberglass Filled Body

- Combining the strength and light weight of a reinforced nylon with the aesthetics of polished stainless steel.
- Tested according to ASTM D638 and ASTM D790.
- Suitable for above waterline outlets.



Part number	A (mm)	B	C	D	E (max mm)
M7-04-9005256	19	82	33	48	28
M7-04-9005258	38	112	41	60	29
M7-04-9005262	19	63	33	48	10
M7-04-9105418	16	63	33	48	10
M7-04-9105419	25	95	33	48	22
M7-04-9105420	51	115	56	82	20

