PRODUCT PAGE

For technical and availability information, please contact Onmar.
+46 (0) 16 42 86 80
info@onmar.se
www.onmar.se

SNAP IN PLUNGER



OB-10-2010-50/
OB-10-2015-50

OB-10-1005-50


Nylon & Rubber & PP

- Compact design for versatile applications on seat cushions, hatches, electric panels, etc.
- Different holding power can be customized upon request.
- OB-10-1005-50: Engagement can be adjusted by reversing or removing the spacer under catch.
- OB-10-1005-50: 32 mm cutout is required.
- OB-10-2010-50 and OB-10-2015-50: 50 mm cutout is required.
- Reusable marking punch is required for proper installation and warranty will be voided in the event one is not used. Marking punch should be replaced after prolonged use to ensure ongoing proper alignment during installation.
- Stainless steel 304 accessories are included.

PATENTED



Marking Punch





OB-10-1005-50 CATCH HEIGHT

Without Spacer	With Spacer	Reverse Spacer
		
11(7/16")	13.5(1/2")	16(5/8")
Tighter Engagement		Looser Engagement

Part number	A *(mm)*	B	C	D	E	Cut-out	Holding power
OB-10-1005-50	46	3~13	39	13,5	13	32	8 kg
OB-10-2010-50	62	3~19	60	27	25,4	50	10 kg
OB-10-2015-50	62	3~19	60	27	25,4	50	17 kg
OB-10-9001	Aluminum Marking Punch for OB-10-1005-50 and OB-10-2010-50						
OB-10-9002	Aluminum Marking Punch for OB-10-2015-50						

INSTALLATION INSTRUCTION

1



Snap in.

2



Tighten screw.

3



Insert marking punch to mark for alignment.

4



Install male part and hold in place.